

Description	Specifications
IN/Out Connectors	19 pin HDMI female type-A
HDCP pass thru	Yes
Single Link Range	480 P, 720i/P, 1080i/P
Video Data Rate	6.75 Gbps
Vertical Frequency Scan Rate	24/50/60 Hz
Dimension	2.1 x 2.5 x 1.1 inch
DC adapter (included)	6 / 9VDC, 500mA



For Questions and support:

Email : info@octavainc.com

URL: www.octavainc.com

User's Guide

Copyright© 2008 Octava Inc. All rights reserved.

HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LL.C

All trademarks are the sole property of their respective companies

Application Diagram



Installation:

- 1) Connect the HDMI Input cable (the one connected to your DVD or Settop Box) to the HDMI IN of the Extender.

Note. The Extender should be installed so the long HDMI cable is at the Input and the short HDMI cable is between the HDMI output of the Extender and your Display.

- 2) Connect the TV Display to the HDMI OUTPUT using the short HDMI/DVI cable.
- 3) Connect the DC power adapter
- 4) The Blue LED should be ON.

Description:

Do you have a long HDMI or DVI cable link between the source and projector monitor that is causing your video to drop out. This compact HDMI Cable Equalizer automatically equalizes and compensates for HDMI/ DVI cables losses and extends cable reach to projectors or monitors. This HDMI / DVI Equalizer can be powered directly from the cable without an external power supply so is ideal for projection theatre systems. An external power adapter is supplied for long cable applications.

HDMI is backward compatible with DVI.

Features:

- Extends cable reach to projectors or monitors
- Extends cable reach to 100ft. Perfect for projector systems
- Compatible with 480p, 720i/p, 1080i/p
- Compatible with VGA, SVGA, XGA, SXGA, UXGA
- Low power, powered directly from most HDMI sources
- Easy to use. Plug and Play.
- DVI compatible with use of adapters.